

# RAVAS-310

## A PALLET TRUCK SCALE FROM THE LEADER IN MOBILE WEIGHING

INCREASES EFFICIENCY AND SIMPLIFIES LOGISTIC PROCESSES, SAVES TIME AND SPACE

NTEP-APPROVED INTEGRATED PRINTER STANDARD

BACKLIGHT INDICATOR FOR EASIER READ OUT

FOR CHECKING INCOMING GOODS, DOSING AND MIXING, DETERMINING SHIPPING WEIGHTS, COUNTING PARTS AND DATA COMMUNICATION

PIECE COUNTING PROGRAM WITH PIECE WEIGHT SAMPLING

THREE DIFFERENT COMMUNICATION PROTOCOLS FOR DATA TRANSFER TO HANDHELD TERMINAL, PC OR WMS

HIGH ACCURACY: MAXIMUM ERROR 0.1% OF THE APPLIED WEIGHT

EASILY EXCHANGEABLE BATTERY PACK FOR CONTINUOUS USE; CHARGER INCLUDED



#### FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic and manual tare
- Totalling with sequence number
- ID-code entry (5-digit)
- Piece counting by sampling
- Piece counting by entry of piece weight
- Printing of date, time, counted pieces, gross/net weight, total weight
- Internal clock
- Error messages in display
- Automatic shut off after 30 minutes of non-use
- Lbs/kg toggle function

Standard NTEP approved (Legal for Trade), industrial exchangeable battery pack and integrated thermal printer.



### DIMENSIONS

DIMENSIONS						
<ul> <li>A Fork length</li> <li>B Fork width</li> <li>C Minimum fork height Minimum space between floor and forks</li> <li>D Maximum fork height</li> </ul>	103°				B	
Lifting height E Width over forks F Height to top indicator	: 4.75 inch/120.65 mm : 27 inch/68.58 CM : 30 inch/76 mm		5			
PRECISION STANDARD VERSION						
Max. inaccuracy : 0.1% of the	applied weight					
Graduation : 5000 lbs: gr	aduation 2.0 lbs	F L	N			
STANDARD SPECIFICATIONS			A <u></u>		also a	D
Weighing capacity : NTEP appro graduation s	oved 5000 lbs x 2 lb	•			2-5- m	С
	0.7 inch, with backlight and			A	B	
Keypad : 5 function k on / off key, zero	eys; piece counting, print, tare,					
Printer : Thermal prin		Ī	Indicator 310		]	
Protection class : load cells and cabling NEMA 5, indicator NEMA 4			Print example	-		
Steering wheels : polyurethan			CODE 12 B/G	2345 1234 lb		
Loading wheels : polyurethan	e, single		Б/G T	34 lb		
	000), epoxy painted		N	1200 lb		
Own weight : 285 lbs	Ab inductrial bottom, pool	-				
Battery : 12 Vdc / 1.2 Ah industrial battery pack, exchangeable and rechargeable; charger		1	Piece counting	example		
included	de ana reenargeable, enarger		PcWt	1200 lb		
Battery life : 35 hours, lo	w voltage indication	(	Qty	1200 Pcs		
	: 230 Volt / 12 Vdc - 300 mA		Total print example			
Charging time : approximately 6 hours			Total print exam Tot. B/G	1234 lb		
Pump : quick lift			Tot. T	34 lb		
			Tot. N	1200 lb		
		1	Nr.	1		

10/07/06

#### \*\*\*\*\*\*\*\*\*\*\*\*\*

17:45

E

#### **OPTIONS WEIGHING SYSTEM**

- Bluetooth<sup>®</sup> signal output
   RAVAS SIR Mobile software for integration with Microsoft Windows<sup>®</sup> CE 5.0 / Mobile 5.0 platforms

- □ NTEP approval 3000 lbs x 1 lb
- Multi-range graduation:
  - 0-500 lbs x 0.5 lb 500-1000 lbs x 1 lb
  - 1000-5000 lbs x 2 lbs
- □ Extra exchangeable battery

#### **OPTIONS HAND PALLET TRUCK**

□ Width over forks 21 inch

